4smarts
the innovation brand

product data sheet

Wall Charger PDPlug SiC 65W 1C and USB-C Cable DigitCord 1,5m, white



- **SiC Technology:** Advanced SiC-based power semiconductors, as used in electric mobility – delivering high efficiency, precise power control and reliable performance
- **65W Fast Charging:** Powerful USB-C charging for smartphones, tablets and many USB-C laptops
- **Compact Travel Design:** High charging performance in a space-saving design – ideal for everyday use, work and travel
- **Single USB-C Port:** Full charging power for one device – simple, efficient and reliable
- **Display right at your device:** Read the current charging power in watts live at the connector

Item no.	EAN/GTIN	SRP
541990	4252011915613	36,90 €

specifications

Master Data	
Product Type	Wall charger
Color	white
Material	Polycarbonate (PC), Acrylonitrile butadiene styrene (ABS), Metal
Product Dimensions in cm	3,50 x 3,00 x 7,70
Product Weight in kg	0.109
Series	PDPlug
Warranty Period	24 months
Scope of Delivery	1x Wall Charger PDPlug 65W SiC 1C, white, 1x USB-C Cable DigitCord 100W 1.5m
Compatibility	Compatible with USB-C devices supporting Power Delivery (PD) up to 65W. Suitable for smartphones, tablets, and light to mid-sized laptops such as the MacBook Air, MacBook Neo, and comparable models. For high-performance laptops (e.g., MacBook Pro under heavy load), charging performance may be limited. MacBook Pro 14"(M6)
Charging & Power	
Input	Euro plug (Typ C), AC 100–240V 50/60Hz 1.5A Max.
Number of USB Ports	1
Output 1	USB-C1, DC 5V/3A - 15W, 9V/3A - 27W, 12V/3A - 36W, 15V/3A - 45W, 20V/3.25A - 65W Max. AVS: 9V-15V/3A - 45W, 15V-20V/3.25A - 65W Max. PPS: 5V-11V/5A - 55W Max.
Max Power (Watt)	65W
Average Operating Efficiency	84.4 %
Efficiency at Low Load (10%)	82.5 %
Power Consumption at No Load	0.18 W
Fast Charging Protocol	Hisilicon FCP, Apple 2.4A, Qualcomm® Quick Charge™ 3.0, USB Power Delivery PPS, USB Power Delivery 3.2, Universal Fast Charging Specification (UFCS), Samsung Adaptive Fast Charge (AFC), Huawei Super Charge (SCP), Adjustable Voltage Supply (AVS)
Protection Circuits	Over Current Protection (OCP), Over Voltage Protection (OVP), Short Circuit Protection (SCP), and Over Temperature Protection (OTP)
Product-Specific Features	
Special Features	SiC technology
Shipping & Logistics	
TARIC Code	85044083
Packaging Dimensions in cm	9.50 x 4.00 x 10.50
Shipping Weight in kg	0.137

product data sheet

Wall Charger PDPlug SiC 65W 1C and USB-C Cable DigitCord 1,5m, white

Packaging	Retail packing with euro hole
Packaging Ecology	plastic free